

Hand Held Digital Pyranometer



“Instrumex” make Handheld Pyranometer (Solar Radiation Recorder) reflect state of the art in micro controller based instrumentation design. The Pyranometer sensor can be attached with this handheld terminal for the collection of real time data Manually/automatically (user selectable). The terminal has its internal memory along with, a real time clock with an LCD (16 X 2) to display the instrument status. It is a self-contained power source system, fitted with 2XAA Alkaline type batteries with battery level display, complete with sensor mounted on a levelling Base Plate. Sensor powered directly from Handheld terminal and no need of external power source. 4 x 2 keypad is provided for programming data logger and monitoring sensor reading at site without the help of computer. Can store up-to 9 different sites data with Site ID. USB port is provided for data downloading from terminal to Computer/Laptop. Data file is saved in Microsoft’s Excel Format.



Features & Specifications

Sensor Input: One Pyranometer Sensor

Parameter Monitored: Date, Time, Solar Radiation (W/m²).

Display: LCD (16 X 2) to display the instrument status.

Keyboard: provided for on-site programming.

Logging: Manual / Automatic (User Selectable) Interval 1 Sec to 24 hrs

PC Software: GUI based Instrumex-ware software for Data download.

Real Time Clock: Internal with accuracy of +/- 2 minutes /year & leap year compensation

Application Software (Instrumexware)

This is a user-friendly, Menu Driven, Windows based software allows you to view & save collected data from data logger to computer/laptop. Data file is saved in Microsoft’s Excel format.



Hand Held Digital Pyranometer

Specifications

Memory: more than 12000 data sets (at user selectable interval).
 Battery : 2XAA Alkaline Batteries (easily replaceable onsite).
 Battery Monitoring: Battery Level display on LCD with Low Battery Warning
 Operating Humidity: 0 to 100%, Operating Temp: - 20 to 70 °C
 Data Port: USB Port for Downloading Data from Data Logger to Computer/Laptop.
 Data Output Format MS- Excel

Deliverables

1. Pyranometer Sensor with 1m cable length
2. Programmed Handheld Terminal/Data Logger
3. 2 batteries (type AA)
4. USB cable
5. software

Sensor Options (Choose Any One)

Solar Radiation Sensor (For Shortwave Radiation)



Radiation Range: 0 – 2000 w/m²
 Cosine response @ 45° zenith angle: ± 4 %
 Cosine response @ 75° zenith angle: ± 10 %

Solar Radiation Sensor (For Global Radiation)



ISO classification second class
 Spectral range 285 - 2800 nm
 Sensitivity (nominal) 15 μV/ W.m⁻²

Hand Held Digital Pyranometer

Absolute accuracy: $\pm 5 \%$

Repeatability: $\pm 1 \%$

Output: 0.200 mV / Wm⁻²

Sensitivity: Custom calibrated to exactly 5.00 W m⁻²/ mV

Operating environment - 40 to 55 °C; 0 to 100% RH

Calibration traceability WRR

Temperature range -40 - +80 °C

Range 0 to 2000 W.m⁻²

Temperature dependence < 0.1%/°C

Ordering Guide

SN	Description	Model No.
1	Digital Pyranometer with Shortwave Radiation Sensor	HDP-VH-SR
2	Digital Pyranometer with Global Radiation Sensor	HDP-VH-GR

DUQE Square Business Centre, Quarter
Deck, Queen Elizabeth 2, Mina Rashid,
Dubai (United Arab Emirates)

Tel. +971-525829733

E-mail: sales@instrumex.ae

Represented by

****Drawing/specifications are subjected to change at any time without prior notice as per manufacturing suitability.**